

# tesa® 4968

Double-sided filmic tape

PRODUCT INFORMATION

## Product Description

tesa® 4968 is a white double-sided self-adhesive tape consisting of a PVC-backing and a tackified acrylic adhesive.

tesa® 4968 features especially:

- An outstanding adhesion level even to critical low surface energy materials such as PP and PE
- Immediate functionality of the laminated bond due to excellent initial tack
- Light and age-resistant acrylic adhesive

## Main Application

- Mounting of non-heated exterior car mirrors onto the holding plate
- Mounting of mouldings and decorative trim parts in the furniture industry

## Technical Data

■ Backing material	PVC film	■ Type of adhesive	tackified acrylic
■ Colour	white	■ Elongation at break	130 %
■ Total thickness	295 µm	■ Tensile strength	30 N/cm

## Adhesion to

■ Steel (initial)	10.5 N/cm	■ Steel (after 14 days)	27.0 N/cm
■ ABS (initial)	12.1 N/cm	■ ABS (after 14 days)	21.5 N/cm
■ Aluminium (initial)	10.3 N/cm	■ Aluminium (after 14 days)	20.7 N/cm
■ PC (initial)	13.8 N/cm	■ PC (after 14 days)	24.6 N/cm
■ PE (initial)	4.9 N/cm	■ PE (after 14 days)	7.5 N/cm
■ PET (initial)	9.6 N/cm	■ PET (after 14 days)	22.4 N/cm
■ PP (initial)	6.5 N/cm	■ PP (after 14 days)	12.7 N/cm
■ PS (initial)	11.9 N/cm	■ PS (after 14 days)	18.2 N/cm
■ PVC (initial)	10.6 N/cm	■ PVC (after 14 days)	21.7 N/cm

## Properties

■ Temperature resistance short term	70 °C	■ Resistance to chemicals	+
■ Tack	+	■ Softener resistance	o
■ Ageing resistance (UV)	+	■ Static shear resistance at 23°C	+
■ Humidity resistance	++	■ Static shear resistance at 40°C	o

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=04968>

Page 1 of 2 / As of 07/08/14

### tesa SE

Quickbornstraße 24  
20253 Hamburg  
Germany  
Phone: +49 (40) 4909 101

tesa SE

A Beiersdorf Company

<http://www.tesa.com>

### tesa tape inc.

5825 Carnegie Boulevard  
Charlotte, N.C. 28209  
United States of America  
Phone: +1 (704) 554 0707  
Fax: +1 (704) 553 5634  
<http://www.tesatape.com>

### tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive  
#04-01 The Metropolis  
Tower 1  
Singapore 138588  
Tel: +65 6697 9888  
Fax: +65 6659 6390  
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.

**Additional Info**

Liner variants:  
PV0 brown glassine paper (71 µm)  
PV6 red MOPP-film (80 µm)

For latest information on this product please visit <http://l.tesa.com/?ip=04968>

Page 2 of 2 / As of 07/08/14

**tesa SE**

Quickbornstraße 24  
20253 Hamburg  
Germany  
Phone: +49 (40) 4909 101

**tesa SE**  
A Beiersdorf Company

<http://www.tesa.com>

**tesa tape inc.**

5825 Carnegie Boulevard  
Charlotte, N.C. 28209  
United States of America  
Phone: +1 (704) 554 0707  
Fax: +1 (704) 553 5634  
<http://www.tesatape.com>

**tesa tape Asia  
Pacific Pte. Ltd.**

9 North Buona Vista Drive  
#04-01 The Metropolis  
Tower 1  
Singapore 138588  
Tel: +65 6697 9888  
Fax: +65 6659 6390  
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.