

tesa® 54190 Precision Die Cuts

High performance decorative film for Black Out Design and Permanent Protection of sensitive surfaces

PRODUCT INFORMATION

Product Description

The self adhesive tape consist of a black PVCfilm coated with a pure acrylic adhesive. tesa® 54190 can be applied for exterior and interior decorative purposes in the automotive industry.

The product features perfect optical appearance and long lasting adhesion properties. It can also be applied for the permanent protection of car parts from mechanical damage and to seal holes in the car body work.

The film can be shaped when heated and can also be used on 3D-surfaces.

Main Application

tesa® 54190 is designed for exterior and interior decorative application and permanent protection around the car body. This tape has a perfect visual appearance and long lasting adhesion properties on painted surfaces.

The product is also perfectly suitable for BSR-Applications.

Technical Data

Backing material	PVC film	Elongation at break	250 %
Colour	black	Tensile strength	60 N/cm
Total thickness	185 µm	Type of liner	PE-coated paper
Type of adhesive	acrylic	Colour of liner	white
Adhesion to Steel (initial)	8.5 N/cm	Weight of liner	138 g/m²

Properties

Matt surface finish	yes	Scratch resistance	++		
Temperature resistance	+	UV-resistance	++		
Abrasion resistance	+	Temperature resistance	+		
Resistance to chemicals	++	Abrasion resistance	+		
Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low					

Additional Info

tesa® 54190 can be supplied individually to customer specification in various dimensions. Under the product number tesa® 7190, the material is also available as rolls.

For latest information on this product please visit http://l.tesa.com/?ip=54190

Page 1 of 1 / As of 07/17/14

tesa SE

Quickbornstraße 24 20253 Hamburg

5825 Carnegie Boulevard Charlotte, N.C. 28209 United States of America

tesa tape inc.

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive #04-01 The Metropolis Tower 1

http://www.tesatape.com http://www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.