

tesa® 54678

Precision die cuts for hole covering applications

PRODUCT INFORMATION

Product Description

tesa® 54678 die cuts consist of polyethylene extruded cloth based on a 45 mesh woven PET/ rayon fabric which is coated with a natural rubber adhesive. Die cuts are supplied on a yellow glassine liner.

Main Application

At assembly line for exterior and interior hole covering on all car body areas.

Technical Data

■ Backing material	PE extruded cloth	■ Elongation at break	8 %
■ Total thickness	250 µm	■ Tensile strength	50 N/cm
■ Type of adhesive	natural rubber	■ Temperature resistance (30 min)	95 °C
■ Adhesion to steel	4.25 N/cm	■ Mesh	45 count per square inch

Properties

■ Hand tearability	++	■ Suitable for die cutting	yes
■ Straight tear edges	+	■ Abrasion resistance	+

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

Additional Info

We would like to recommend our stock assortment, which includes the following dimensions:
circles: 19 / 30 / 40 / 50 mm diameter

tesa® 54678 is available upon request in customer specific dimensions and can be delivered in either roll form or as sheets.

For latest information on this product please visit <http://l.tesa.com/?ip=54678>

Page 1 of 1 / As of 07/04/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

<http://www.tesa.com>

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
<http://www.tesatape.com>

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.