

tesa® 4215

PVC-free fineline tape for design painting

PRODUCT INFORMATION

Product Description

tesa® 4215 is a high quality PVC-free fineline tape with a rubber adhesive. It is designed for applications where sharp colour edges for two-tone designs are required.

- very flexible for narrow curves and difficult 3D-dimensions
- no edge lifting off and removable without leaving any residues
- easy unwinding, also suitable for overmasking
- translucent
- non-halogen

Main Application

Masking & Design, for a wide range of fineline applications

Technical Data

Backing material	PE film	Elongation at break	350 %
Total thickness	130 µm	Tensile strength	19 N/cm
Type of adhesive	natural rubber	Temperature resistance (PP-	120 °C
Adhesion to steel	2.5 N/om	FPDM)	

Temperature resistance (paint)

Properties

Hand tearability	++	Powerwash resistance	++		
Easy to remove	yes	Conformability	++		
Paint anchorage	++	Flame retardant	++		
Sharp colour edge	++	Conformability	++		
Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low					

Additional Info

Fineline tape can be applied by hand or by using dispensers, die cuts are available as tesa® 54215

For latest information on this product please visit http://l.tesa.com/?ip=04215

Page 1 of 1 / As of 07/04/14

120 °C

tesa SE

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

5825 Carnegie Boulevard Charlotte, N.C. 28209 United States of America

tesa tape inc.

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive #04-01 The Metropolis Tower 1 Singapore 138588 Phone: +1 (704) 554 0707 Tel: +65 6697 9888 Fax: +1 (704) 553 5634 Fax: +65 6659 6390 http://www.tesatape.com http://www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.