

tesa® 4318 PV2

High performance paper masking tape up to 160 °C

PRODUCT INFORMATION

Product Description

tesa® 4318 PV2 is a finely crêped, flexible paper masking tape, especially suitable for the high requirements of paintworks (water- or solvent based paints) followed by oven-drying.

Technical Data

■ Backing material	slightly-creped paper	■ Elongation at break	12 %
■ Total thickness	170 µm	■ Tensile strength	47 N/cm
■ Type of adhesive	natural rubber	■ Temperature resistance	160 °C
■ Adhesion to steel	4 N/cm		

Properties

■ Hand tearability	++	■ Sharp colour edge	+
■ Easy to remove	yes	■ Conformability	+
■ Paint anchorage	++		

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

Additional Info

Paints and even critical filler systems adhere very well to the backing avoiding any kind of flaking.

tesa® 4318 PV2 can be removed from rubber, glass and paint without leaving adhesive residues.

For latest information on this product please visit <http://l.tesa.com/?ip=04318>

Page 1 of 1 / As of 07/04/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

<http://www.tesa.com>

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
<http://www.tesatape.com>

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.