

tesa® 7133

Surface protection and masking tape

PRODUCT INFORMATION

Product Description

tesa® 7133 is a self-adhesive polypropylene tape with a natural rubber adhesive.

Main Application

- Protection against dirt and damage of painted and unpainted parts
- Masking during multi color painting

Technical Data

■ Backing material	PP film	■ Elongation at break	30 %
■ Total thickness	80 µm	■ Tensile strength	133 N/cm
■ Type of adhesive	natural rubber	■ Temperature resistance	120 °C
■ Adhesion to steel	2 N/cm		

Properties

■ Easy to remove	yes	■ Scratch resistance	++
■ Paint anchorage	++	■ Flame retardant	++
■ Powerwash resistance	++		

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=07133>

Page 1 of 1 / As of 07/04/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

<http://www.tesa.com>

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
<http://www.tesatape.com>

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.