

# tesa Bodyguard® 50535 PV8

Temporary protection tape for freshly painted surfaces

## PRODUCT INFORMATION

### Product Description

tesa Bodyguard® 50535 PV8 is the best protection solution for freshly painted car bodies. Applied after the painting process, tesa Bodyguard® 50535 PV8 provides reliable protection for painted surfaces susceptible to damage. Due to the good UV-resistance and perfect paint compatibility, tesa Bodyguard® 50535 PV8 is the most reliable way to protect cars during the transportation process.

Features & benefits:

- Reliable protection
- Secure adhesion also at lower temperatures
- Secure adhesion during transport
- Cost savings as polishing or repair after demasking is eliminated
- Paint protection during outdoor storage up to 12 months
- Easy to apply and remove
- Easy disposal - both the film and the adhesive system are environmentally friendly

### Main Application

- Protection of painted surfaces during the assembly, storage and transportation process

### Technical Data

■ Backing material	polyolefinic film	■ Elongation at break	450 %
■ Total thickness	61 µm	■ Tensile strength	25 N/cm
■ Type of adhesive	EVA	■ UV-resistance	52 weeks
■ Adhesion to steel	0.6 N/cm		

### Properties

■ Easy to remove	yes	■ Paint compatibility	++
■ Suitable for die cutting	yes	■ Resistance to chemicals	++

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=50535>

Page 1 of 1 / As of 07/04/14

#### tesa SE

Quickbornstraße 24  
20253 Hamburg  
Germany  
Phone: +49 (40) 4909 101

**tesa SE**  
A Beiersdorf Company

<http://www.tesa.com>

#### tesa tape inc.

5825 Carnegie Boulevard  
Charlotte, N.C. 28209  
United States of America  
Phone: +1 (704) 554 0707  
Fax: +1 (704) 553 5634  
<http://www.tesatape.com>

#### tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive  
#04-01 The Metropolis  
Tower 1  
Singapore 138588  
Tel: +65 6697 9888  
Fax: +65 6659 6390  
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.