

tesa® Assemblyguard 50540

Temporary protection tape for freshly painted carbodies

PRODUCT INFORMATION

Product Description

tesa® Assemblyguard 50540 is a premium grade self-adhesive tape that has been developed for the protection of delicate surfaces, e.g. painted metal surfaces during automotive assembly.

The product consists of an air bubble film coated with a paint compatible adhesive. Applied after the painting process, tesa® Assemblyguard 50540 provides reliable protection for painted surfaces susceptible to damage during the assembly process. Due the cross perforation of the product it is easily hand tearable without using any cutting devices.

tesa® Assemblyguard 50540 is recommended for indoor applications only.

Main Application

- Protection of painted surfaces during the assembly process

Technical Data

■ Backing material	polyolefinic film	■ Type of adhesive	EVA
■ Total thickness	4200 µm	■ Adhesion to steel	0.5 N/cm

Properties

■ Easy to remove	yes	■ Paint compatibility	++
■ Suitable for die cutting	yes	■ Resistance to chemicals	+

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=50540>

Page 1 of 1 / As of 07/04/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

<http://www.tesa.com>

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
<http://www.tesatape.com>

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.