

tesa® 51136

Surface protection and masking tape

PRODUCT INFORMATION

Product Description

tesa® 51136 is a self-adhesive polyethylene tape with an acrylic adhesive for masking large areas of plastic parts during professional painting processes. The colour of the tape provides a good contrast to dark surfaces making the positioning easier and faster. Furthermore tesa® 51136 is an interior protection tape for slightly structured surfaces. tesa® 51136 PV2 is a higher adhesion version for rough surfaces and carpets.

Main Application

- Masking during painting applications
- Protection of various surfaces against dirt and damage

Technical Data

■ Backing material	PE film	■ Elongation at break	300 %
■ Total thickness	105 µm	■ Tensile strength	19 N/cm
■ Type of adhesive	acrylic	■ Temperature resistance	100 °C
■ Adhesion to steel	2.4 N/cm		

Properties

■ Easy to remove	yes	■ Scratch resistance	+
■ Paint anchorage	++	■ Flame retardant	++
■ Powerwash resistance	++		

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=51136>

Page 1 of 1 / As of 07/15/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

<http://www.tesa.com>

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
<http://www.tesatape.com>

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.